

PROJETO DE AERONAVES
AIRCRAFT DESIGN – 10403

2019/2020



PACKAGE DELIVERY LIGHT UAV

UAV-19

Project Description

CONTENTS

1. INTRODUCTION	3
2. REQUIREMENTS.....	4
2.1. Mission	4
2.2. Performance	4
2.3. Propulsion	4
2.4. Wings	5
2.5. Fuselage.....	5
2.6. Tail	5
2.7. Landing Gear	5
2.8. Payload	5
2.9. Weight and Balance.....	5
2.10. Controls and Systems	6
2.11. Design Airworthiness Requirements	6
3. TASKS	6
3.1. Concept of Operations	6
3.2. Layout.....	6
3.3. Aerodynamics and Stability	6
3.4. Propulsion and Performance	7
3.5. Systems.....	7
3.6. Structure and Materials.....	7
3.7. Time plan.....	7
3.8. Work Requirements.....	8
4. ASSESSMENT.....	9
4.1. Test.....	9
4.2. Presentation.....	9
4.3. Report.....	9
4.4. Exam	9
4.5. Grade	9
5. REFERENCES	10
5.1. Text Book	10
5.2. Aircraft Design Books	10
5.3. Other Books	10

1. INTRODUCTION

The international aerospace sector has increasingly used in recent years unmanned aerial vehicles (UAV - Unmanned Aerial Vehicle) for missions of various types, such as: aerial photography, military reconnaissance, atmospheric research at high altitude, radio communication, surveillance, fire detection, technology development, etc.. Despite the technology involved, UAVs have dimensions smaller than manned aircraft, making their operation more flexible and more economical. The increasing automation and communication capabilities and the evolution of available materials has allowed the operation of these aircraft at distances and altitudes greater than ever, increasing their potential by making them equal, or even superior, to other aircraft that need to carry on board systems for crew support. For short distance surveillance applications, the investment required for the development and operation of a UAV is comparatively lower than equivalent manned aircraft so that its use in these tasks results in a cost-benefit ratio much more attractive. The UAV sector is the only sector of the aerospace industry with significant growth in the last 30 years, with an average growth rate of over 14% per year.

The UAV sector is rapidly flourishing and in many cases it is a source of concepts and technologies for manned aircraft. Currently, most UAVs in operation have military applications. The use of UAVs in civil applications is, however, growing rapidly with the appearance of new concepts of operation and the creation and maturation of appropriate legislation. Portugal needs to stay in this important aerospace area in order to be more autonomous in the development of technological means essential to the sustainability of its resources and its regional and national economic maturity, to employ its qualified manpower and to be a competitive exporter of technology.

Portugal also needs the use of UAVs in various areas of activity. Monitoring of forest areas which in recent years have succumbed to fires is an important example. The application of surveillance unmanned aerial vehicles allows a high degree of uptime and availability in the tasks of this nature and is a complementary means of ground surveillance and satellite monitoring already in use. The application of new UAV concepts to new civil scenarios that can be economic viable is also important.

In the past few years electric propulsion for aircraft has seen tremendous developments and a widespread use. Its application ranges from the model aircraft, UAVs, sailplanes, ultralight and general aviation aircraft. Because batteries have a limited energy density, resulting in flights of short duration, the use of fuel cells for battery charging is an interesting option that has already been exploited. Conventional propulsion with a piston engine allows flights with longer duration and with the help of an alternator coupled to the engine batteries, that provide on-board power for systems, can be recharged in flight. To avoid consumption of gasoline to produce electricity, the incorporation of photovoltaic cells on the aircraft can provide part or all of the electrical energy required on board. In some situations a hybrid propulsion system may be preferred.

The main objective of this subject is to show students what the conceptual design of an aircraft is and what steps are necessary to follow given mission and performance requirements, design constraints, design methods and the need for optimization. To achieve this, the knowledge gained will be applied to the design of a new aircraft subjected to specific requirements. The optimization of the project is of extreme importance in the development of a new aircraft.

This project description presents the requirements that the aircraft must respond to in terms of mission, configuration, performance, systems, materials and design standards. It also

describes the necessary tasks to be performed during the semester and the work plan to follow. This project requires dedication and continuous work to ensure that deadlines are met and results lead to a good design.

2. REQUIREMENTS

The current requirements present a need for an autonomous UAV (also capable of being remotely piloted) with the capability to fly efficiently over a relatively long distance to deliver high priority packages over a regional area. The requirements for this aircraft are listed below and during the course of the project they must be respected. Possible changes in the requirements will be discussed and agreed upon by the teacher and all the elements involved in the project.

It is required to perform the conceptual and preliminary design of a UAV taking into account some specific design requirements. The aircraft must have good flying qualities to allow easy and precise flying. The vehicle's structure and aerodynamics must be carefully designed to achieve low power consumption levels. Simplicity, robustness and ease of repair are essential to maintain high levels of operational readiness of the UAV.

2.1. Mission

The UAV must be designed for the following mission: it must take-off from an airfield (or be launched by external means), then climb to a cruise altitude of no less than 500 m, cruise for at least 80 km to the destination, drop the payload and return to base. The objective of the operation is to deliver high priority packages to isolated areas (small villages, farms, or groups of people) within a regional area of 80 km in diameter in a timely and efficient manner. The payload covered in this need comprises medicines or food with a mass varying from 1 kg to 5 kg. The turnaround time should be as low as possible yet less than 10 minutes to allow for urgent package dispatching.

It is desirable, though not mandatory, to have a vehicle that can complete the journey through as many destinations as possible in the area given above during the daylight period in a Winter day in Central Europe (around 8 hours). There may be a centrally placed base from which the vehicle operates and to which it returns at the end of the journey.

The vehicle should be able to be disassembled into part of no more than 1 m in length, so that it can fit in a typical car boot.

2.2. Performance

The vehicle must show the following performance figures (ISA conditions):

Take-off	from an airfield (less than 60 m) or external launcher
Cruise speed	above 80 km/h
Maximum speed	at least 100 km/h
Flight operational radius	at least 80 km
Data link range	at least 80 km (or satellite)
Operational ceiling	at least 1000 m
Landing	on an airfield (less than 120 m) or other means

2.3. Propulsion

Electric motors and/or piston engines may be selected for this UAV. The possibility of integrating a hybrid propulsion system can be considered for improved flexibility and increased range. The propellers must be selected to match the motor/engine performance according to the UAV performance required. The aircraft can either have tractor or pusher propellers and can have as many propulsion units as required. In selecting the motor/engine, careful attention must be given to its durability and reliability. Proper cooling of the motor/engine must be provided. Tilting of the motors/engines may be considered (or not) to fulfil specific operational needs.

2.4. Wings

The wings must be well designed, both aerodynamically and structurally, so that the overall efficiency of the vehicle is high and to allow the required mission to be accomplished with low energy requirements. According to the mission, the wings must be designed for high lift-to-drag ratio. The structure should use high specific strength and high specific stiffness materials to allow for an empty weight as low as possible. A tilting wing may be considered in conjunction with tilting motors/engines if and when applicable.

2.5. Fuselage

The fuselage should be slender and light, yet possess the necessary internal space for systems and payload. It should have high tolerance on payload weight and position. Equipment substitution and payload access should be quick and simple to perform. A separate pod for the payload may be considered. The payload compartment should be capable of carrying a container which holds the cargo in a proper manner. The payload compartment should have at least the reference dimensions 250 mm × 100 mm × 100 mm (length × width × height) and should be accessed very quickly to load and unload the package container.

2.6. Tail

The tail, when present, must be small and effective. It should use in their structure the same materials selected for the wings.

2.7. Landing Gear

The choice of using a landing gear will depend on the concept of operation proposed. If it exists, it must be rugged, yet simple.

2.8. Payload

The payload (up to 5 kg) must be well secured in the fuselage to avoid any movement during flight. The payload can be considered as a container holding the high priority cargo. For some types of package, such as medicines or food, the container must be well insulated in terms of temperature.

2.9. Weight and Balance

The centre of gravity (CG) travel must be such that no negative impact on the stability

or on the normal operation of the UAV is imposed for any payload weight transported on board. It is important that the maximum take-off mass of the UAV is kept as low as possible not exceeding 15 kg. The vehicle should be capable of flying without any payload.

2.10. Controls and Systems

The control system will include autopilot boards (or at least physical space for those) which are not required to be selected. Control surfaces, tilting surfaces and motor/engine's tilting mechanisms if applicable must be sized and must be actuated by servo mechanisms. All electronic and electric components and mission equipment must be placed within the fuselage according to their function and in such a way as to allow its quick preparation or replacement. The electric system should be powered by batteries which can be charged by an alternator driven by the engine in a conventional or hybrid propulsion configuration.

2.11. Design Airworthiness Requirements

The design airworthiness requirements that should be used in the structural sizing are the EASA CS-VLA, CS-LSA or CS-23. The design manoeuvre limit load factors are, in principle, +3 and -3, but those should be checked with a V-n diagram. All work performed in the design should aim at achieving high levels of safety and performance.

3. TASKS

There are several tasks in the design project that must be carried out according to the time plan below. All tasks depend on each other so that there must be a close interaction and updating between them. The design process is also iterative in nature but perfection is not possible nor is necessary but an effort must be put forward to achieve a good optimization level in the outcome.

The necessary calculations may be performed with the help of spread sheets and also other analysis computer programs. All drawings should be, preferably, done in CATIA V5.

3.1. Concept of Operations

The exact mission profile and the way it is going to be operationally implemented must be defined and explained. The design of the vehicle will follow from the concept of operations (CONOPS) proposed to respond to the mission requirements.

3.2. Layout

The layout and functionalities of the vehicle must be selected so that the requirements are fully met. This task is very important because it integrates all needs of the other parts of the project into a viable configuration. A preliminary three dimensional (3D) study of all major components must be performed and these must be incorporated in the aircraft structure. 3D drawings must be produced in a CAD system for the complete UAV.

3.3. Aerodynamics and Stability

The aerodynamic study must cover the selection of the aerofoils, geometry and size of

the lifting surfaces, nacelles and the computation of the aerodynamic characteristics of the whole vehicle (C_L , C_D e C_M). It must be assured that all choices made in the overall design do not impair the aerodynamic performance. A study of the stability and control of the UAV must also be performed.

The aerodynamic work must concentrate on the wings design and tail sizing. These must be optimized having in mind the necessary compromises for different flight conditions.

3.4. Propulsion and Performance

The propulsive system (motor, propeller, power source, fuel system) must be selected and sized according to the requirements. An estimate of the vehicle's performance (speeds, times, battery and/or fuel usage, etc.) must be carried out.

3.5. Systems

A study of the landing gear system (if it exists), of the control system and of the electric system must be performed. These studies should include not only the selection of the main components and definition of its functionalities but also the positioning of components and routing of cables inside the aircraft. Commercially available components are preferred to speed up both design and building processes. A database containing such data as suppliers, working characteristics, weight, power consumption and price of all components selected must be produced.



3.6. Structure and Materials


The type of structure and materials for the different components of the vehicle must be selected and defined adequately keeping in mind their configuration and function. Preliminary sizing of the wing must be performed. A database containing such data as suppliers, physical characteristics, mechanical characteristics and price of all materials selected must be produced. A study on the manufacturing processes to be used must be carried out together with estimates of weight and balance and total cost of the UAV.

3.7. Time plan

The table below presents the time plan with the tasks required to complete de project.

Month	S	S	O	O	O	O	O	N	N	N	N	D	D	D	D	J	J	J	J	J	F	F
Task \ Week	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22
Lectures																						
Layout																						
Aerodynamics/Stability																						
Propulsion/Performance																						
Systems																						
Structure/Materials																						
Test																						
Presentation																						
Report																						
Exams																						

Legend:  Lectures
 Design work



3.8. Work Requirements

The design is carried out by groups of 5 students. In order for the project objectives to be fulfilled in time all students should work hard.

	Student's Name	Nº	Team	E-mail	Task
01					layout
02					aerodynamics/stability
03					propulsion/performance
04					systems
05					structures/materials
06					layout
07					aerodynamics/stability
08					propulsion/performance
09					systems
10					structures/materials
11					layout
12					aerodynamics/stability
13					propulsion/performance
14					systems
15					structures/materials
16					layout
17					aerodynamics/stability
18					propulsion/performance
19					systems
20					structures/materials
21					layout
22					aerodynamics/stability
23					propulsion/performance
24					systems
25					structures/materials
26					layout
27					aerodynamics/stability
28					propulsion/performance
29					systems
30					structures/materials
31					layout
32					aerodynamics/stability
33					propulsion/performance
34					systems
35					structures/materials
36					layout
37					aerodynamics/stability
38					propulsion/performance
39					systems
40					structures/materials
41					layout
42					aerodynamics/stability
43					propulsion/performance
44					systems
45					structures/materials

4. ASSESSMENT

The grade of this subject is given based on one written test (T), one oral presentation (P) and one report (R).

4.1. Test

The test covers all the topics discussed during classes up to the date of the test (16 December 2019 – week 14). The test is divided into two parts: the first is closed book and the second is open book.

4.2. Presentation

Near the end of the semester there will be an oral presentation of the project (6 January 2019 – week 17). In the presentation, when the project is almost complete, each design team (all elements of the team must participate in the presentation) must show to the other teams that their design meets all requirements and explain the steps that led to the final concept. This presentation should take 20-30 minutes for each team, depending on the number of teams that exist.

4.3. Report

Each team must write up a design report that should contain all relevant steps taken in the UAV design process, including layout, decisions made, major calculations, results, etc.. Sketches necessary to fully understand the design and a three view drawing with all major dimensions and aircraft characteristics should also be included. The number of pages is limited to around 30, using letter size 12 and single line spacing. The report should be handed in *pdf* format at the last day of lectures together with the original CAD drawings (10 January 2019 – week 17).

4.4. Exam

There will be no written exam. If students fail the “Frequência” assessment or wish to improve their final grade, they must hand in an improved report of their design project at the dates of the exam, in weeks 19 or 21.

4.5. Grade

The mark of this subject is given by $F = 0.3T + 0.2A + 0.5R$ and approval is obtained if $F \geq 10$. The same is true for the exam final mark.

1.	Frequência ($F = 0.3T + 0.2A + 0.5R$)			100
	T	Test	16-12-2019 (09h30)	30
	A	Presentation	06-01-2020 (09h00)	20
	R	Report	10-01-2020 (24h00)	50
2.	Exam ($E = 0.3T + 0.2A + 0.5 R1$)			100
	R1	Report (normal period)	??-01-2020 (09h30)	50
	R1	Report (recourse period)	??-02-2020 (09h30)	50

4.	Exam ($E = 0.3T + 0.2A + 0.5 R2$)	100
R2	Report (special period)	??-07-2020 (??h00) 50

5. REFERENCES

The books listed below can be used for the design. The design reports of previous years may also be useful as general guideline and source of ideas. However, one must bear in mind that the information contained in them may be incorrect. A lot of information can also be found in the internet using appropriate search criteria.

5.1. Text Book

01. Raymer, D. P., *Aircraft Design: A Conceptual Approach* - 4rd edition, AIAA Education Series, 2006

5.2. Aircraft Design Books

02. Gundlach, J., *Designing Unmanned Aircraft Systems: A Comprehensive Approach*, AIAA Education Series, 2012
03. Stinton, D., *The Design of the Aeroplane*, Blackwell Science, 1983
04. Jenkinson, Lloyd R., Marchman III, James F., *Aircraft Design Projects for Engineering Students*, Butterworth-Heinemann, 2003
05. Barros, C., *Introdução ao Projecto de Aeronaves* – Volumes 1 & 2, CEA/UFGM, 1979
06. Brandt, S. A., Stiles, R. J., Bertin, J. J., Whitford, R., *Introduction to Aeronautics: A Design Perspective*, AIAA Education Series, 1997
07. Corke, T. C., *Design of Aircraft*, Pearson Education, Inc., 2003
08. Howe, D., *Aircraft Conceptual Design Synthesis*, Professional Engineering Publishing, 2000
09. Jenkinson, L. R., Simpkin, P., Rhodes, D., *Civil Jet Aircraft Design*, Arnold, 1999
10. Pazmany, L., *Light Airplane Design*, Pazmany Aircraft Corporation, 1963
11. Roskam, J., *Airplane Design* – Volumes I to VIII, The University of Kansas, 1990
12. Torenbeek E., *Synthesis of Subsonic Airplane Design*, Delft University Press, 1982

5.3. Other Books

13. Abbot & Doenhoff, *Theory of Wing Sections*, Dover Publications Inc, 1959
14. Barnaby Wainfan, *Airfoil Selection – Understanding and Choosing Airfoils for Light Aircraft*, 1988
15. Barnes W. McCormick, *Aerodynamics, Aeronautics and Flight Mechanics* – 2nd edition, John Wiley & Sons Inc, 1995
16. Bernard Etkin, Lloyd Duff Reid, *Dynamics of Flight, Stability and Control* – 3rd edition, John Wiley & Sons Inc., 1996
17. Bill Clarke, *The Cessna 172* – 2nd edition, Tab Books, 1993
18. Darrol Stinton, *Flying Qualities and Flight Testing of the Airplane*, AIAA Education Series, 1996
19. David A. Lombardo, *Aircraft Systems – Understanding Your Airplane*, Tab Books, 1988
20. Euroavia, *Future Trainer Concept*, 1999
21. Geoff Jones, *Building and Flying Your Own Plane*, Patrick Stephens Limited, 1992

22. Ian Moir & Allan Seabridge, *Aircraft Systems*, Longman Scientific & Technical, 1992
23. *Jane's All the World Aircraft*, 1995
24. JAR-23, *Joint Aviation Requirements for Normal, Utility, Aerobatic and Commuter Category Aeroplanes*, JAA, 1994
25. JAR-27, *Joint Aviation Requirements for Small Rotorcraft*, JAA, 1993
26. JAR-VLA, *Joint Aviation Requirements for Very Light Aeroplanes*, JAA, 1990
27. Ladislao Pazmany, *Landing Gear Design for Light Aircraft – Volumes I & II*, Pazmany Aircraft Corporation, 1986
28. John Cutler, *Understanding Aircraft Structures*, Blackwell Science, 1999
29. Martín Cuesta Alvarez, *Vuelo con Motor Alternativo*, Paraninfo, 1981
30. Robert C. Nelson, *Flight Stability and Automatic Control*, McGraw-Hill, 1989
31. S. Hoerner, *Fluid-Dynamic Drag*, Hoerner Fluid Dynamics, 1965
32. S. Hoerner, *Fluid-Dynamic Lift*, Hoerner Fluid Dynamics, 2nd Edition, 1985
33. Stelio Frati, *L'Aliante*, Editore Ulrico Hoepli, Milano, 1946
34. Ted L. Lomax, *Structural Loads Analysis for Commercial Transport Aircraft – Theory and Practice*, AIAA Education Series, 1996
35. *The Metals Black Book – Volume 1 – Ferrous Metals*, Casti Publishing Inc, 1995
36. *The Metals Red Book – Volume 2 – Nonferrous Metals*, Casti Publishing Inc, 1995
37. T. H. G. Megson, *Aircraft Structures for Engineering Students – 2nd edition*, Edward Arnold, 1990
38. Tony Bingelis, *Firewall Forward – Engine Installation Methods*, EAA Aviation Foundation, 1992
39. Tony Bingelis, *Sportplane Construction Techniques – A Builder's Handbook*, EAA Aviation Foundation, 1992
40. Tony Bingelis, *The Sportplane Builder – Aircraft Construction Methods*, EAA Aviation Foundation, 1992